



Model		FS900 (Type: Rubber tires)			
Dimensions	Total length		101.2 in	257 cm	
	Total width		69.7 in	177 cm	
	Total height	Bucket Frame	58.3 in	148 cm	
		Bottom of discharge opening (when bucket raised to the highest level)	58.7 in	149 cm	
Weight	Machine (empty fuel tank	without LED light	1552.1 lb	704 kg	
Minimum turning radius			108.3 in	275 cm	
Engine	Model		Vanguard 356447		
	Туре		Air-cooled 4-cycle gasoline engine		
	Total displacement		34.78 cu.in.	570 cm ³ (0.57 L)	
	Maximum output		13.2 kW (18.0 PS)/3,600 rpm		
Fuel tank capacity			Gasoline 5.28 U.S.gal.	Gasoline 20.0 dm³ (20.0 L)	
Operating width			31.9 in	81 cm	
Bucket capacity			109.3 U.S.gal.	414 dm³ (414 L)	
Drive	Traveling		HST (2WD)		
	Sweeping section		Hydraulic, Mechanical		
Speed (HST)	Forward		0 - 9.9 mph	0 - 16.0 km/h	
	Reverse		0 - 3.1 mph	0 - 5.0 km/h	
Efficiency			1.28 ac/hr(4.97 mph x operating width x 0.8)	$5,184 \text{ m}^2/\text{h}(8.0 \text{ km/h x operating width x } 0.8)$	

Option

LED Light

An optional LED light can be attached. It is useful when driving in the early morning, at dusk, or when visibility is poor due to fog.



※ The factory default maximum engine rpm is 3,000 rpm.



Read the Owner's Operating Manual and other training material carefully. Be familiar with the controls, safety signs and the proper use of equipment before operation.



Assurance inspection

Regular inspection of the machine ensures long-lasting superior performance and safety.
There are parts of machine prone to wear and deterioration from long periods of use.
Please consult with local dealer or distributor for proper inspection and maintenance schedule.





Riding Sweeper / Core Collector









Brush Offset

The brush is mounted in an offset position in order to cleanly collect the core and reduce damage to the turf.





No Double Stepping on the

The front wheel is designed with two separated tires, which enables the front wheel to avoid rolling over and crushing the core twice. Thus, the machine can cleanly sweep up the cores.

In addition, the front tires can avoid treading on the same paths that the rear tires had previously tread on. This effectively prevents ruts from forming.



The Down Pressure Function of the Roller

The FS900's compaction roller can exert a down pressure on the turf.

While collecting cores, it can smooth out unevenness and make tire ruts less noticeable.

Lightweight Design

Lighter than a towed or large sweeper, it is designed to reduce ruts.



Workability

Efficiency



Easy to turn

The three-wheel design with two separate front tires provides excellent turning performance and makes turning around the green



Excellent Mobility

As a small riding type, the FS900 has excellent mobility and can move effortlessly between halls.



Brush Height Adjustment

The height of the brush can be adjusted without a tool. This allows the operator to easily and quickly adjust the height according to the operational conditions or degree of wear-and-tear.



High-Reaching Dump Hopper

The hopper can reach high to dump the cores. The operator doesn't need to get off the machine to discharge the cores into a dump truck, which improves work efficiency.



This makes maintenance easier and improves work efficiency.







Postadress:

TRÄDGÅRDSTEKNIK AB Helsingborgsvägen 578, Varalöv 262 96 ÄNGELHOLM URL:

Telefon: 0431-222 90

Org.nr: 556409-6120

Bg.nr: 5743-7980

www.tradgardsteknik.se

E-postadress:

info@tradgardsteknik.se