

Quality on Demand



LM56 & LM66

Ultimate Pedestrian Greensmower



BEVATTNINGSTEKNIK Helsingborgsvägen 578, Varalöv 262 96 ÄNGELHOLM, SWEDEN Telefon: +46 431 22250

Email: info@bevattningsteknik.se eller philip@bevattningsteknik.se

www.bevattningsteknik.se







Nickel-Chrome-Molybdenum cutting cylinder for extreme long life and bi-directional grooming reel for ultimate flexibility



Single plate friction clutch for smooth pickup, precise control and easy engagement of the all-gear drive



The unique long-life Baroness bedknife, with 4 different lip sections, to enable you to work down to 1.5mm, is reknowned for its durability under the toughest topdressing regimes

, toughton topulousing		
Specification	BARONESS LM56	BARONESS LM66
Cutting width	556mm	646mm
Clip	4mm (250 cuts per metre)	4mm (250 cuts per metre)
Reel Diameter	128mm	128mm
No. of cylinder blades	11	7,9 or 11
Height of cut range	1.5mm to 13mm	7mm to 29mm
Engine	Subaru EX13D 3.2 kW/4.5hp	Subaru EX13D 3.2 kW/4.5hp
Speed	4.8 kph	4.8 kph
Weight Mower - Grassbox - Transport wheels	81kg 3.3kg 6.9kg	86kg 3.3kg 6.9kg
Length (incl. Grassbox)	1500mm	1500mm
Width	942mm	1032mm
Height	1030mm	1030mm



The Baroness LM56 and LM66 can be fitted with three optional accessories - a 78/92 blade grooming reel, a 39/46 blade thatching reel or a 6cm diameter, 49/57cm working width rotating brush.



Quality on Demand

Telefon: 0431-222 90

Org.nr: 556409-6120

Bg.nr: 5743-7980

Postadress:

TRÄDGÅRDSTEKNIK AB Helsingborgsvägen 578, Varalöv 262 96 ÄNGELHOLM **URL:**

www.tradgardsteknik.se

E-postadress:

info@tradgardsteknik.se